



Pressostati TG600

Pressure switches TG600 series

280.35200.10A

PRESSOSTATO DI MASSIMA CON RIARMO MANUALE HIGH-LIMIT PRESSURE SWITCH WITH MANUAL RESET

Dati Tecnici Technical Data

Valore di taratura in fabbrica Factory calibration value	3,5 ±0,2 bar
Riarmo manuale Manual reset	< 2,8 bar
Apertura contatto C/NC con aumento di pressione C/NC contact opens with increasing pressure	
Pressione max. Max pressure	4bar
Grado di protezione Degree of protection	IP00
Portata contatti Contact rating	16 (4)A 250V~ - 6 (1)A 400V~
Durata meccanica Mechanical endurance	100.000 cicli 100.000 cycles
Temperatura ambiente max Ambient temperature max	T120
Temperatura fluido max Fluid temperature max	T120
Attacco Connection	ottone (ch14) R1/4 UNI ISO 7/1 brass (key14) R1/4 UNI ISO 7/1
Involucro Enclosure	PBT
Omologhe Approvals	ENEC 03 - CE



Opzioni Options


Attacchi: R1/8 (ch14) - G1/4 (ch17)
Connections: R1/8 (ch14) - G1/4 (ch17)

Altri attacchi speciali su richiesta
Other special connections on request

Contatti dorati
Golden contacts

Temperatura fluido max = T140
Fluid temperature max = T140

Schemi di collegamento Electrical wiring



Disegno & Dimensioni Drawing & Dimensions

