

# SIMPLY SMART



**FantiniCosmi** 

C800 WIFI

SMART PROGRAMMABLE THERMOSTAT









# **C800** WIFI

SMART PROGRAMMABLE THERMOSTAT









C800 WIFI Q

20,5

SQUARE THERMOSTAT

C800 WIFI R RECTANGULAR THERMOSTAT

205

C800 AL FLUSH MOUNTING

C800 WIFI PRO C800WIFIQ + RECTANGULAR BASE + FLUSH MOUNTING POWER SUPPLY KIT

# DYNAMIC GEOLOCATION


















<sup>(\*)</sup> presently available only in Italy / Italian language.

### **TECHNICAL FEATURES**

Temperature regulation range	2 ÷ 40 °C, increase 0,1°C
Power supply	2 batteries 1,5V AA or 230Vac @50Hz
Contacts rating	5(3)A 250 Vac
Adjustable differential	STD, 0,3 ÷ 5 K
Thermal gradient	4 K/h
Ambient RH display range	0 ÷ 99 %, increase 1%

# **DIMENSIONS** [mm]




## HOMOLOGATION AND STANDARD

- Complies with EN 60730-1 standards;
- Compliant with Directive 2014/53 / UE (RED)
- Class IV; 2% (Reg. EU 811/2013 813/2013)
- C€ EH[

#### INSTALLATION



Wall mounting (for battery supply) or flush mounting in 500 or 502 module boxes (for 230Vac supply).



Wall mounting (for battery supply) or flush mounting in 503 module box (for 230Vac supply).



Available FLUSH MOUNTING POWER SUPPLY KIT 230Vac/3.3Vcc for C800 series.

#### **CODES**

C800WIFIPRO	Smart Programmable Thermostat with power supply kit, square and rectangular bases
C800WIFIQ	Smart Programmable Thermostat with square base
C800WIFIR	Smart Programmable Thermostat with rectangular base
C800AL	Power supply kit 230Vac/3.3Vcc for C800 series











FL-C800WIFI-EN